

## Form Burster



Unbeatable in quality and performance, the Duplo FB-706 Form Burster bursts, trims, decollates, and slits continuous forms and suits any form handling requirement while enhancing the final appearance.

## S P E C I F I C A T I O N S

FORM SIZE	Length 3" - 14" Width 4" - 18" (4" to 17" finished width)
MARGIN SLIT WIDTH	0"-1.125"
SINGLE-PLY FORM CAPACITY	47 - 157 gsm (bond)
MULTI-PLY FORM CAPACITY	8-part carbonless (40 -50 gsm)
SPEED	26 - 410 feet per minute
JOB MEMORY	120 presets
FEATURES	Preset counter; automatic stop at end of form; last page delivery; margin cutting, message display; safety cover with interlock; automatic stop for jams; automatic power off; waste box; manual 10-job form width memory; DSC function; conveyor adjustment; LED margin cut line
POWER REQUIREMENTS	100 - 120V ± 10% 50/60 Hz
MARGIN SLITTER GUIDE LED BATTERY	Lithium battery (CR-2032) x 2 (recommended to be replaced every three years)
OPTIONS	Center Slitter

Production rates are based upon optimal operating conditions and may vary depending on stock and environmental conditions. As part of our continuous product improvement program, specifications are subject to change without notice.

## STANDARD FEATURES

- Ideal for any office environment, the electronic length settings and fixed burst rollers make the FB-706 compact and quiet
- User-friendly control panel allows a quick and easy form length setup. Also features power driven side quides for simple form width setup.
- Built-in light indicators on both margin slitters show where sheets will be slit
- Form job memory stores up to 120 jobs, reducing setup time for commonly used jobs
- Variable speed up to 410 feet per minute
- Large graphic LCD control panel allows easy setup and job view by displaying form count, set lengths, and jams with instructions
- DSC (Dynamic Stability Control) automatically adjusts the roller pressure to keep performance without changing the speed
- Jam detector automatically stops operation in order to protect forms from being damaged
- Interlocking safety cover provides operator safety precautions
- Last form sensor automatically stops operation after last form is burst
- Self diagnostic system for service assistance

## OPTIONAL FEATURE

 Center Slitter ~ provides capability of slitting burst forms in half, necessary when running 2-up applications and slit merging